

**BACKGROUND OF THE INVENTION**

1

2           This application incorporates the subject matter of Provisional Application No.  
3   60/203,722, filed May 12, 2000. All rights to said Provisional Application are claimed herein.

4

5           The present invention relates to a walkway for protecting the movement of airline  
6   passengers to and from aircraft and in particular to a movable ramp passenger walkway for the  
7   protective movement of passengers between the ground and the doorway of the aircraft.

8

9           In my earlier U.S. Pat. No. 5,603,343 there is disclosed a collapsible articulating ground  
10   passageway having a plurality of independent U-shaped frame sections that are articulately  
11   connected in an end to end series to form a flexible corridor. The passageway disclosed in my  
12   prior patent is adapted to communicate with a commuter aircraft at a first end and with the  
13   airport terminal at the other. These passageways were designed and intended for use on the  
14   ground with smaller commuter type aircraft which generally have door still wells below 6 feet.  
15   At present there still is no bridge or pathway apparatus which can dock with a commuter  
16   aircraft with a still well between 6 and 16 feet in height having the capability of extending and  
17   retracting while simultaneously swinging left and right as well as varying in height to meet the  
18   individual still wells of varying sized aircraft.

19

20           It is apparent that numerous innovations for walkways, loading bridges and similar  
21   devices have been provided in the prior art. However, even though these innovations may be  
22   suitable for the specific individual purposes to which they address, they would not be suitable  
23   for the purposes of the present invention as hereinafter described.

24

25           It is therefore, an object of the present invention to provide a passenger walkway

20051002-051104

1 overcoming the disadvantages inherent in the prior art.

2

3 It is an object of the present invention to provide a passenger walkway adapted to  
4 communicate between an airport ground terminal and a varying sized commuter aircraft having  
5 between a "zero" height application to a 16 foot height application.

6

7 It is yet another object of the present invention to provide a passenger walkway easily  
8 moved from one location to another.

9

10 It is still another object of the present invention to provide a passenger walkway with  
11 an integral floor from the terminal to the aircraft.

12

13 It is yet another object of the present invention to provide a passenger walkway can be  
14 easily deployed.

15

16 It is a further object of the present invention to provide a passenger walkway simple and  
17 inexpensive to manufacture and maintain.

18

19

20 The foregoing objects, together with other objects and advantages, will be apparent  
21 from the following disclosure of the present invention.

22

23 **SUMMARY OF THE INVENTION**

24

25 According to the present invention there is provided a walkway having a series of fixed  
26 height corridor sections and a ramp section. The sections are joined in an articulating manner  
27 so that the plurality of corridor sections may be deployed over a long distance as from a  
28 terminal or bus to the aircraft. Each section is provided with a floor to permit passengers to  
29 walk above the ground between the bus and the aircraft. The ramp section is variable in height  
30 to accommodate docking with aircraft of varying heights. A top and side cover of each section  
31 is provided with a weather proof fabric for protection of passengers from inclement weather

1 as they pass to and from the aircraft.

2

3 Full details of the present invention are set forth in the following description and  
4 accompanying illustration of the invention.

5

6 **BRIEF DESCRIPTION OF THE DRAWINGS**

7

8 The invention will be best understood by reference to the following drawings, wherein:

9

10 FIG. 1 is a side elevational view of the ramped passageway according to the present  
11 invention docked at one end to the terminal bus and at its other end to an aircraft;

12

13 FIG. 2 is a perspective view of the frame structure forming the passageway shown in  
14 Fig. 1;

15

16 FIG. 3 is a perspective view of an expanded frame section of the passageway according  
17 to the present invention;

18

19 FIG. 4A is a perspective view of the frame sections shown in Fig. 3 with the frame  
20 section collapsed;

21

22 Fig. 4B is a reverse perspective view of the frame section shown in Fig. 4A;

23

24 Fig. 5 is a front elevational view of the frame section shown in Fig. 3;

25

26 Fig. 6 is a side elevational view of the frame section shown in Fig. 3;

27

28 Fig. 7 is a side elevational view of the frame section shown in Fig. 4B;

29

30 Fig. 8 is a top plan view of the walkway illustrating the articulated relationship between  
31 the sections; and

COPIES OF THIS DOCUMENT

FIG. 9 is a side elevational view of the gangway section showing the various inner elements of the gangway.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

The movable walkway of the present invention depicted by the numeral 10, is generally illustrated in Fig. 1. As illustrated the walkway is installed to permit passengers to walk from a bus 12 (or from a terminal exit) directly to an aircraft 14 waiting on the airport apron 16.

The construction of the walkway 10 is illustrated in Fig. 2, without any enclosure or covering. The walkway 10, thus is formed of frame like skeleton structures divided into a plurality of sections each similar in construction to that shown in my earlier patent, namely a plurality of partially collapsible fixed height corridor sections 22 (only one shown) and an inclined gangway section 24. The corridor sections 22 are articulately connected to each other and to the inclined gangway 24 in sequence, in a manner to be described hereinafter, with respect to Fig. 8.

The construction of each corridor section 22 is shown in detail in Figs. 3. through 7. Each corridor section 22 comprises a plurality of U-shaped supports 26. Preferably, three supports 26 are used, as such number enables construction of a corridor section of optimum length for movement, linear coverage and mass. Each support 26 is formed (Fig. 5) of a pair of vertically disposed tubular legs 28 and a connecting roof arch beam 30. The vertical legs 28 each terminate at their upper ends in a clevis 32 into which the respective ends of the individual arched roof beam 30 seat. The cross-section of the vertical upright legs 28 is somewhat larger than that of the arched roof beam 32 and suitable bolts or pins inserted therethrough hold the arched roof beam 32 fixedly to the upright legs 28 much in the manner shown in my earlier patent.

The U-shaped supports 26 are interconnected by a plurality of horizontal cross braces 34. Generally, the cross braces 34 will be fixed at each of their ends to the vertical legs 28, by

1 suitable bolts or weldments so as to rigidly maintain the vertical supports 26 aligned and  
2 parallel with one another. In this arrangement, the length of each corridor 22 is fixed.  
3 Preferably, however, it is desirable to be able at least to partially collapse the corridor sections  
4 22 so as to reduce their length permitting the overall length of the walkway to be reduced to  
5 meet the distance between bus (or terminal) 12 and the aircraft 14 and to reduce the overall  
6 bulk of the walkway 10 for storage.

7  
8 To affect collapsibility of each corridor section 22 alternate vertical supports 26,  
9 (central support when only three supports are used) are provided with a cuff like guide 36 fixed  
10 in alignment with each of the braces 34. In this manner a three support corridor is divided into  
11 two portions, denominated for conveyance as the anterior A and the posterior B portions. The  
12 set of the braces 34, of the anterior portion are not attached to the center support but freely  
13 move through the corresponding guide 36. In this manner the portions A & B can seemingly  
14 telescope with respect to each other as seen in the figures.

15  
16 A sub-flooring, generally depicted by the numeral 38 is provided as seen in detail in Fig.  
17 2. The sub-flooring 38 comprises an array of longitudinal braces 40 similar to the braces 34  
18 and arranged similarly as described above so that one set of braces 40 slide freely through cuff-  
19 like guides 42 fixed to the corresponding support 26, thus maintaining the collapsibility.

20  
21 Interconnecting the opposed floor brace 40 is an array of longitudinal and transverse  
22 floor beams 44. Each arrangement of braces 40 and floor beams 44 are staggered at different  
23 levels to each other, to maintain collapsibility, by sliding one over the other as seen in Fig. 4a,  
24 4b & 6. The sub-floor is arranged upward of the lower ends 46 of the vertical legs so as to be  
25 spaced from the ground. Each vertical leg 28 is provided with a roller or caster 48 at its lower  
26 end. (for the sake of clarity not all the drawings show the rollers.)

27  
28 The floor of each section is completed by attaching a central deck plate 50 over each  
29 sub floor 38. At the free end of the deck plate 50 in the anterior portion A of each corridor  
30 there is attached an inclined transitional ramp 52, hanging down to the ground. The transitional  
31 ramp 52 is provided with a folded-in bottom 54 forming a lip resting stably on the ground.

1 The free end of the deck plate 50 in the posterior portion B extends as a short shelf like  
2 member 56 adapted to extend outwardly over the adjacent floor in the next sequential corridor  
3 or gangway section. Of course the dimension of the sub-floor 38 and the plate 50 are such that  
4 telescoping movement of the anterior and posterior portions A and B are not hindered. The  
5 transitional ramp 52 and the extensions 56 are provided with holes 57 which will register with  
6 each other on serially arranging the corridors so as to form pivot bearings allow the corridors  
7 22 to articulate or swing relative to each other with a defined arc.

8

9 Returning to Fig. 2, the gangway 24 is constructed having a plurality of vertically  
10 oriented U-shaped supports 58 and horizontal braces 60, similar to those used in formation of  
11 the rigid fixed section 22, except that they increase in height from the anterior end 62 where  
12 they are aligned and equal in height to those forming the corridor section 22 to a height at its  
13 posterior end 64 capable of fully enclosing the doorway opening of any commuter or small  
14 aircraft. A second distinction between the gangway 24 and the corridor 22 lies in the fact that  
15 the frame structure is not collapsible and the braces 60 are fixedly on the vertical supports held  
16 at each end as well as between the ends to form a fixed length passageway.

17

18 The gangway 24 is provided with a raisable sub-floor, generally depicted by the numeral  
19 66 formed of parallel side beams and a plurality of cross beams in the arrangement of a ladder.  
20 The sub-floor 66 is pivotally attached at its rear anterior end 68 to the lower beams of the  
21 gangway 24 so as to be raisable at its posterior end 64, by means of a carriage assembly 70  
22 slideably mounted in the lower most anterior brace 72, which is formed in the shape of a c-  
23 channel. (see also Fig. 9.)

24

25 Secured over the sub-flooring 66 is one or more deck plates 74, forming a continuous  
26 ramp from the anterior end, 68 to the posterior end 64. At the posterior end 64, an auxiliary  
27 deck plate 76 extends forwardly to form a continuous extension ramp through the gangway 24.

28

29 At the extreme forward end of the gangway passage 24 there is located a horizontal  
30 stable platform 78, which is guided within a pair of horizontally opposed rails 80, so as to be  
31 able to reciprocally slide between a first position cantilevered outward from the gangway

0051002-051101

1 passage 24 to a second storage position within the gangway 24. The rails 80 are themselves  
2 guided by vertical tracks 82 and are connected to the posterior end of the sub-flooring 66, by  
3 a curved hinge 84 (Fig. 9).

4

5 The stable platform 78 is raised and lowered selectively by a scissor type elevating  
6 mechanism 86. The upper and lower ends of the scissor 86 ride is horizontal rails 88, fixed to  
7 the lower portion of the vertical support, while the upper ends of the scissors 86, ride in the  
8 respective horizontal rails 80. The scissor 86 is actuated by a reversible electric motor 90 and  
9 screw transmission system 92 to elevate the platforms 78 and the forward end of the sub-floor  
10 66. Having the anterior end 68 of the sub-floor mounted in a slidable carriage 70 avoids  
11 binding or other problems, as the sub-floor 66 is raised at the posterior end.

12

13 In this manner an inclined ramp 94 is formed within the gangway 24 which can be  
14 elevated to the proper height of the aircraft door and whereby the stable platform 78 can be  
15 extended to abut the door sill providing a smooth walking transition for the passengers from  
16 ground level to aircraft level.

17

18 As seen in Fig. 8 the anterior end of the inclined gangway 24 is provided with an  
19 extended tongue 100, which passes beneath the posterior shelf 56 of the adjacent corridor  
20 section 22, and is pinned thereto so as to permit the inclined gangway 24 to swing in an  
21 articulating arc. Fig. 8, also shows the pivot pin arranged between the aligned corridor section  
22 22.

23

24 As seen in Fig. 2, there is provided a laterally extending bracket 102 fixed to the lower  
25 most portion of the posterior end of the gangway 24. This bracket 102 is employed to allow  
26 a motive drive device such as an electric cart to be hooked thereto enabling the operator of the  
27 cart to easily maneuver and move the walkway.

28

29 The corridor and inclined gangway sections 22 and 24 are covered in the manner  
30 described in my earlier patent with a fabric cover capable of maintaining suitable condition  
31 within the walkway no matter the anterior weather condition. The fabric may be provided with

